## NSN 5940-01-484-9063

Terminal Board - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5940-01-484-9063

Mounting Hole Diameter:
0.160 inches
Body Style:
Barrier type
Terminal Row Quantity:
2
Center To Center Distance Between Terminals:
0.375 inches
Distance Between Terminal Row Centers:
0.313 inches
Board Construction:
Solid construction
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.875 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.313 inches
Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:
0.406 inches
Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:
0.141 inches
Boardlength:
2.157 inches
Boardwidth:
1.125 inches
Boardheight:
0.609 inches
Board Height Excluding Terminals:
0.328 inches
Base Thickness:
0.328 inches
End Application:
An/tsq-131, radar and iff systems
Current Rating In Amps:
15.0
Mounting Facility Type And Quantity:
4 unthreaded hole
Terminal Pattern Arrangement:
Multi-row
Special Features:
Voltage rating: 600 v max; maximum watts per terminal: 3750; maximum wire size is no. 16; operating temperature: -55 degrees to +300
degrees f
Material:
Plastic phenolic board

## NSN 5940-01-484-9063

Terminal Board - Page 2 of 2



_	•		_	-		
<b>ن</b>	ırfa	$\sim$	I rc	nter	nor	٠.

Tin terminals

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A011b0