

View Online at <https://aerobasegroup.com/nsn/5940-01-488-9728>

**Dielectric Withstanding Voltage In Volts:**

3000.0

**Body Style:**

Barrier type

**Mounting Slot Length:**

0.281 inches

**Mounting Slot Width:**

0.219 inches

**Terminal Row Quantity:**

2

**Center To Center Distance Between Terminals:**

0.531 inches

**Distance Between Terminal Row Centers:**

0.812 inches

**Board Construction:**

Hollow construction without insulated strip

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

6.000 inches

**Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:**

0.906 inches

**Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:**

0.250 inches

**Boardlength:**

6.500 inches

**Boardwidth:**

1.812 inches

**Boardheight:**

0.844 inches

**Board Height Excluding Terminals:**

0.781 inches

**Base Thickness:**

0.375 inches

**End Application:**

Filters, nuclear reactor boundry area

**Current Rating In Amps:**

40.0

**Mounting Facility Type And Quantity:**

2 slot

**Nonfeedthru Terminal Type:**

598 single

**Nonfeedthru Terminal Quantity:**

10 single

**Terminal Pattern Arrangement:**

Multi-row staggered

**Terminal Design:**

Nonfeedthru

**Special Features:**

F in part number indicates a temperature rating of 155 degrees c

**Material:**

Plastic board

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A011b0