

View Online at <https://aerobasegroup.com/nsn/5940-01-490-7310>

Mounting Hole Diameter:

0.223 inches

Dielectric Withstanding Voltage In Volts:

4000.0

Body Style:

Barrier type

Terminal Row Quantity:

2

Center To Center Distance Between Terminals:

0.560 inches

Distance Between Terminal Row Centers:

0.510 inches

Board Construction:

Hollow construction without insulated strip

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.843 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.510 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.410 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.200 inches

Boardlength:

3.281 inches

Boardwidth:

1.330 inches

Boardheight:

0.700 inches

Board Height Excluding Terminals:

0.700 inches

Base Thickness:

0.460 inches

End Application:

2350-01-456-7884; fighting vehicle systems, bradley (bfvs)

Current Rating In Amps:

30.0

Mounting Facility Type And Quantity:

4 unthreaded hole

Terminal Connecting Link Quantity:

4 single

Nonfeedthru Terminal Type:

857 single

Terminal Connecting Link Type:

1 single

Nonfeedthru Terminal Quantity:

4 single

Terminal Pattern Arrangement:

Multi-row

Terminal Design:

Linked nonfeedthru

Special Features:

Rated voltage: 600 volts max; grade f temperature rating 150 c per mil-m-14

Material:

Plastic board

Surface Treatment:

Nickel terminals

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A011b0