

View Online at <https://aerobasegroup.com/nsn/5940-01-493-9068>

**Body Style:**

Barrier type

**Mounting Slot Length:**

0.375 inches

**Mounting Slot Width:**

0.218 inches

**Terminal Row Quantity:**

2

**Center To Center Distance Between Terminals:**

0.652 inches

**Distance Between Terminal Row Centers:**

1.000 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

6.210 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.000 inches

**Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:**

0.250 inches

**Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:**

0.355 inches

**Boardlength:**

6.920 inches

**Boardwidth:**

2.000 inches

**Boardheight:**

1.250 inches

**End Application:**

5411-01-436-3326

**Current Rating In Amps:**

75.0

**Mounting Facility Type And Quantity:**

4 slot

**Terminal Pattern Arrangement:**

Multi-row

**Special Features:**

Terminal designation: brass bar with high pressure solderless connectors; wire range: no. 16 awg to no. 4 awg; 600 volts; continuous use temp: 130 degrees c; flammability rating: 94 v-0; thru-bolt barrier-type construction; unique bar and traveling collar design

**Material:**

Plastic polyester board

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A011b0