

View Online at <https://aerobasegroup.com/nsn/5940-01-514-5207>

Mounting Hole Diameter:

4.3 millimeters

Body Style:

Barrier type

Terminal Row Quantity:

2

Center To Center Distance Between Terminals:

11.1 millimeters

Distance Between Terminal Row Centers:

11.2 millimeters

Board Construction:

Solid construction

Boardlength:

63.8 millimeters

Boardwidth:

34.8 millimeters

Boardheight:

19.1 millimeters

Board Height Excluding Terminals:

19.1 millimeters

Base Thickness:

9.5 millimeters

End Application:

Motor controller panel

Current Rating In Amps:

20.0

Mounting Facility Type And Quantity:

4 unthreaded hole

Nonfeedthru Terminal Type:

857 single

Nonfeedthru Terminal Quantity:

4 single

Terminal Pattern Arrangement:

Multi-row

Terminal Design:

Nonfeedthru

Product Name:

Terminal block, 20 amp, 600 volt, double row terminals, insulated base, panel mount

Special Features:

Made from general purpose phenolic rated ul class 94v-1 or injection grade general purpose phenolic, rated ul class 94v-0

Material:

Plastic phenolic board

Surface Treatment:

Tin terminals or nickel terminals

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A011b0