

View Online at <https://aerobasegroup.com/nsn/5940-01-514-5212>

**Mounting Hole Diameter:**

4.3 millimeters

**Body Style:**

Barrier type

**Terminal Row Quantity:**

2

**Center To Center Distance Between Terminals:**

11.1 millimeters

**Distance Between Terminal Row Centers:**

11.2 millimeters

**Board Construction:**

Solid construction

**Boardlength:**

74.7 millimeters

**Boardwidth:**

34.8 millimeters

**Boardheight:**

19.1 millimeters

**Board Height Excluding Terminals:**

19.1 millimeters

**Base Thickness:**

9.5 millimeters

**End Application:**

Motor controller panel

**Current Rating In Amps:**

20.0

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Nonfeedthru Terminal Type:**

857 single

**Nonfeedthru Terminal Quantity:**

5 single

**Terminal Pattern Arrangement:**

Multi-row

**Terminal Design:**

Nonfeedthru

**Product Name:**

Terminal block, 20 amp, 600 volt, double row terminals, insulated base, panel mount

**Special Features:**

Made from general purpose phenolic rated ul class 94v-1 or injection grade general purpose phenolic rated ul clas 94v-0

**Material:**

Plastic phenolic board

**Surface Treatment:**

Tin terminals or nickel terminals

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A011b0