

View Online at <https://aerobasegroup.com/nsn/5940-01-518-6905>

**Dielectric Withstanding Voltage In Volts:**

600.0

**Body Style:**

Barrier type

**Mounting Slot Length:**

0.310 inches

**Mounting Slot Width:**

0.210 inches

**Center To Center Distance Between Terminals:**

0.562 inches

**Board Construction:**

Solid construction

**Terminal Facility Quantity:**

3

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.250 inches

**Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:**

0.330 inches

**Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:**

0.215 inches

**Boardlength:**

2.680 inches

**Boardwidth:**

0.870 inches

**Boardheight:**

1.050 inches

**Board Height Excluding Terminals:**

0.570 inches

**Base Thickness:**

1.050 inches

**End Application:**

Virginia class submarine, ssn-774

**Current Rating In Amps:**

50.0

**Mounting Facility Type And Quantity:**

2 slot

**Feedthru Connection End Type:**

857 both ends single combination

**Nonfeedthru Terminal Type:**

857 first

**Feedthru Terminal Quantity:**

3 single combination

**Nonfeedthru Terminal Quantity:**

3 second

**Terminal Pattern Arrangement:**

Single row

**Terminal Design:**

Feedthru

**Product Name:**

Series b4000 single row terminal blocks

**Special Features:**

Terminal top: number 10 screw, terminal bottom: number 8 screw, wire range cu: 10-16 awg

**Material:**

Plastic board

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A011b0