

View Online at <https://aerobasegroup.com/nsn/5940-01-518-6905>

Dielectric Withstanding Voltage In Volts:

600.0

Body Style:

Barrier type

Mounting Slot Length:

0.310 inches

Mounting Slot Width:

0.210 inches

Center To Center Distance Between Terminals:

0.562 inches

Board Construction:

Solid construction

Terminal Facility Quantity:

3

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.250 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.330 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.215 inches

Boardlength:

2.680 inches

Boardwidth:

0.870 inches

Boardheight:

1.050 inches

Board Height Excluding Terminals:

0.570 inches

Base Thickness:

1.050 inches

End Application:

Virginia class submarine, ssn-774

Current Rating In Amps:

50.0

Mounting Facility Type And Quantity:

2 slot

Feedthru Connection End Type:

857 both ends single combination

Nonfeedthru Terminal Type:

857 first

Feedthru Terminal Quantity:

3 single combination

Nonfeedthru Terminal Quantity:

3 second

Terminal Pattern Arrangement:

Single row

Terminal Design:

Feedthru

Product Name:

Series b4000 single row terminal blocks

Special Features:

Terminal top: number 10 screw, terminal bottom: number 8 screw, wire range cu: 10-16 awg

Material:

Plastic board

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A011b0