

View Online at <https://aerobasegroup.com/nsn/5940-01-518-7251>

Mounting Hole Diameter:

0.130 inches

Dielectric Withstanding Voltage In Volts:

300.0

Body Style:

Barrier type

Terminal Row Quantity:

2

Center To Center Distance Between Terminals:

0.250 inches

Distance Between Terminal Row Centers:

0.250 inches

Board Construction:

Hollow construction without insulated strip

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.250 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.190 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.130 inches

Boardlength:

4.500 inches

Boardwidth:

0.630 inches

Boardheight:

0.320 inches

Board Height Excluding Terminals:

0.320 inches

Base Thickness:

0.220 inches

End Application:

Tc junction

Current Rating In Amps:

5.0

Mounting Facility Type And Quantity:

4 unthreaded hole

Terminal Connecting Link Quantity:

8 single

Nonfeedthru Terminal Type:

857 single

Terminal Connecting Link Type:

1 single

Nonfeedthru Terminal Quantity:

16 single

Terminal Pattern Arrangement:

Multi-row

Terminal Design:

Linked nonfeedthru

Product Name:

Kulka 410 gp series, 300 volt, double row terminal block

Material:

Copper alloy terminals

Material Specification:

Mil-p-19833, type gdi-30f military specification single material response board

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A011b0

Mil-std (military Standard):

Mil-p-19833 spec.