

View Online at <https://aerobasegroup.com/nsn/5940-01-518-7251>

**Mounting Hole Diameter:**

0.130 inches

**Dielectric Withstanding Voltage In Volts:**

300.0

**Body Style:**

Barrier type

**Terminal Row Quantity:**

2

**Center To Center Distance Between Terminals:**

0.250 inches

**Distance Between Terminal Row Centers:**

0.250 inches

**Board Construction:**

Hollow construction without insulated strip

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

4.250 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.250 inches

**Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:**

0.190 inches

**Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:**

0.130 inches

**Boardlength:**

4.500 inches

**Boardwidth:**

0.630 inches

**Boardheight:**

0.320 inches

**Board Height Excluding Terminals:**

0.320 inches

**Base Thickness:**

0.220 inches

**End Application:**

Tc junction

**Current Rating In Amps:**

5.0

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Terminal Connecting Link Quantity:**

8 single

**Nonfeedthru Terminal Type:**

857 single

**Terminal Connecting Link Type:**

1 single

**Nonfeedthru Terminal Quantity:**

16 single

**Terminal Pattern Arrangement:**

Multi-row

**Terminal Design:**

Linked nonfeedthru

**Product Name:**

Kulka 410 gp series, 300 volt, double row terminal block

**Material:**

Copper alloy terminals

**Material Specification:**

Mil-p-19833, type gdi-30f military specification single material response board

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A011b0

**Mil-std (military Standard):**

Mil-p-19833 spec.