

View Online at <https://aerobasegroup.com/nsn/5940-01-523-7753>

Mounting Hole Diameter:

0.128 inches

Body Style:

Strip type

Terminal Row Quantity:

2

Center To Center Distance Between Terminals:

0.219 inches

Distance Between Terminal Row Centers:

0.750 inches

Board Construction:

Scored for easy breaking into smaller terminal boards

Terminal Quantity Per Section:

10

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.875 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.750 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.125 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.125 inches

Boardlength:

3.130 inches

Boardwidth:

1.000 inches

Board Thickness:

0.063 inches

Mounting Facility Type And Quantity:

4 unthreaded hole

Section Quantity:

2

Nonfeedthru Terminal Quantity:

20 single

Terminal Pattern Arrangement:

Multi-row

Terminal Design:

Nonfeedthru

Special Features:

Item made from 2 segments of scored turret terminal board

Special Markings:

Original identification number shall be obliterated without damage to part then mark in permanent and legible manner iaw mil-std-130: with narrow end up, odd numerals from 1 to 19 down left row and even numbers from 2 to 20 down right row; marked: r2 between and slightly above 3 & 4, r3 between and slightly above 5 & 6, and d1 between and slightly above 7 & 8; mark: 53711-7386571 on package or container

Material:

Glass board

Material Specification:

Mil-i-24768/27, type g-10. 300 f maximum military specification single material response board

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A011b0

Mil-std (military Standard):

Mil-i-24768 spec.