

View Online at <https://aerobasegroup.com/nsn/5940-01-523-7753>

**Mounting Hole Diameter:**

0.128 inches

**Body Style:**

Strip type

**Terminal Row Quantity:**

2

**Center To Center Distance Between Terminals:**

0.219 inches

**Distance Between Terminal Row Centers:**

0.750 inches

**Board Construction:**

Scored for easy breaking into smaller terminal boards

**Terminal Quantity Per Section:**

10

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.875 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.750 inches

**Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:**

0.125 inches

**Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:**

0.125 inches

**Boardlength:**

3.130 inches

**Boardwidth:**

1.000 inches

**Board Thickness:**

0.063 inches

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Section Quantity:**

2

**Nonfeedthru Terminal Quantity:**

20 single

**Terminal Pattern Arrangement:**

Multi-row

**Terminal Design:**

Nonfeedthru

**Special Features:**

Item made from 2 segments of scored turret terminal board

**Special Markings:**

Original identification number shall be obliterated without damage to part then mark in permanent and legible manner iaw mil-std-130: with narrow end up, odd numerals from 1 to 19 down left row and even numbers from 2 to 20 down right row; marked: r2 between and slightly above 3 & 4, r3 between and slightly above 5 & 6, and d1 between and slightly above 7 & 8; mark: 53711-7386571 on package or container

**Material:**

Glass board

**Material Specification:**

Mil-i-24768/27, type g-10. 300 f maximum military specification single material response board

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A011b0

**Mil-std (military Standard):**

Mil-i-24768 spec.