NSN 5940-01-523-9902

Terminal Board - Page 1 of 2

Mounting Hole Diameter:

0.210 inches



View Online at https://aerobasegroup.com/nsn/5940-01-523-9902

| Dielectric Withstanding Voltage In Volts: |
|---|
| 600.0 |
| Body Style: |
| Barrier type |
| Center To Center Distance Between Terminals: |
| 0.570 inches |
| Board Construction: |
| Solid construction |
| Single Feedthru Receptacle Quantity: |
| 7 |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 4.500 inches |
| Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility: |
| 0.210 inches |
| Boardlength: |
| 4.910 inches |
| Boardwidth: |
| 0.750 inches |
| Boardheight: |
| 1.160 inches |
| Board Height Excluding Terminals: |
| 0.720 inches |
| Base Thickness: |
| 0.410 inches |
| Current Rating In Amps: |
| 30.0 |
| Mounting Facility Type And Quantity: |
| 2 unthreaded hole |
| Feedthru Connection End Type: |
| 513 both ends single combination |
| Feedthru Terminal Quantity: |
| 7 single combination |
| Terminal Pattern Arrangement: |
| Single row |
| Terminal Design: |
| Feedthru |
| Product Name: |
| Single row terminal block |
| Special Features: |
| Furnished with 0.164-32 binder head, phil-slot screws; acceptable wire size is no. 12 awg to no. 14 awg |
| |

NSN 5940-01-523-9902

Terminal Board - Page 2 of 2



| M | lat | Or | וכו | |
|---|-----|----|-----|--|
| | | | | |

Plastic phenolic board

Surface Treatment:

Copper alloy terminals

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A011b0