

View Online at <https://aerobasegroup.com/nsn/5940-01-524-4281>

Mounting Hole Diameter:

0.156 inches

Body Style:

Strip type

Terminal Row Quantity:

6

Center To Center Distance Between Terminals:

0.750 inches

Distance Between Terminal Row Centers:

0.375 inches

Board Construction:

Solid construction

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.250 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.250 inches

Boardlength:

9.500 inches

Boardwidth:

3.500 inches

Board Thickness:

0.090 inches

End Application:

Stabilator/sas test unit

Mounting Facility Type And Quantity:

6 unthreaded hole

Terminal Pattern Arrangement:

Multi-row

Product Name:

Component board, stabilator/sas test unit

Special Features:

M1 column of terminals along left edge (see marking for spacing), 6 rows of 3 terminals centered, 0.38, 0.76, and 4.18 inches above bottom mounting holes, and 0.38, 0.76 and 4.18 inches above middle mounting holes

Special Markings:

With short end up, on front: "cr designator" across top edge, letters "a b c d" equally spaced above first row of terminals, "a3" centered along bottom edge, and numerals from 22 to 12 in descending order from bottom edge up, along left edge, beginning 0.38 inch above bottom mounting hole and spaced 0.38 inch apart, and numerals from 11 to 1 in descending order from 0.38 inch above left, center mounting hole to top edge, spaced 0.38 inch apart; on back: "terminal desig" across top edge and letters "e f g h" equally spaced across first row of terminals

Material:

Glass fiber board and plastic epoxy board

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A011b0

Mil-std (military Standard):

Mil-p-18177 spec.