

View Online at <https://aerobasegroup.com/nsn/5940-01-524-9628>

Mounting Hole Diameter:

0.250 inches

Body Style:

Barrier type

Terminal Row Quantity:

2

Center To Center Distance Between Terminals:

0.690 inches

Distance Between Terminal Row Centers:

0.630 inches

Board Construction:

Hollow construction with insulated strip

Center To Center Distance Between Mounting Facilities Parallel To Length:

6.190 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.630 inches

Boardlength:

6.620 inches

Boardwidth:

1.810 inches

Boardheight:

0.940 inches

Board Height Excluding Terminals:

0.750 inches

Base Thickness:

0.440 inches

End Application:

Static exciter/regulator panel assembly, 60 hz lpd-4, sse, 125-17 kw

Current Rating In Amps:

50.0

Mounting Facility Type And Quantity:

4 unthreaded hole

Terminal Connecting Link Quantity:

10 single

Nonfeedthru Terminal Type:

597 single

Terminal Connecting Link Type:

18 single

Nonfeedthru Terminal Quantity:

8 single

Terminal Pattern Arrangement:

Multi-row

Terminal Design:

Linked nonfeedthru

Product Name:

Kulka 603 gp series stud terminal block

Special Features:

Studs extend 0.50 inch above base; threads are 10-32 nf

Material:

Plastic phenolic board

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A011b0