

View Online at <https://aerobasegroup.com/nsn/5940-01-525-5576>

Mounting Hole Diameter:

0.180 inches

Body Style:

Barrier type

Terminal Row Quantity:

2

Center To Center Distance Between Terminals:

0.300 inches

Distance Between Terminal Row Centers:

0.310 inches

Board Construction:

Hollow construction with insulated strip

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.380 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.310 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.125 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.140 inches

Boardlength:

3.660 inches

Boardwidth:

0.870 inches

Boardheight:

0.560 inches

Board Height Excluding Terminals:

0.560 inches

Base Thickness:

0.250 inches

End Application:

Engine dsl

Current Rating In Amps:

15.0

Mounting Facility Type And Quantity:

4 unthreaded hole

Terminal Connecting Link Quantity:

8 single

Nonfeedthru Terminal Type:

857 single

Terminal Connecting Link Type:

18 single

Nonfeedthru Terminal Quantity:

8 single

Terminal Pattern Arrangement:

Multi-row

Terminal Design:

Linked nonfeedthru

Product Name:

Kulka 600 gp series double row terminal block

Special Features:

150 degrees c; screws: no. 5-40 binder head, phil-slot; wire range: no. 12-22 awg; terminals are plated brass

Material:

Plastic phenolic board

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A011b0