

View Online at <https://aerobasegroup.com/nsn/5940-01-525-9468>

Mounting Hole Diameter:

0.170 inches

Dielectric Withstanding Voltage In Volts:

300.0

Body Style:

Barrier type

Terminal Row Quantity:

2

Center To Center Distance Between Terminals:

0.380 inches

Distance Between Terminal Row Centers:

0.310 inches

Board Construction:

Solid construction

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.700 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.380 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.085 inches

Boardlength:

3.688 inches

Boardwidth:

0.875 inches

Boardheight:

0.484 inches

Board Height Excluding Terminals:

0.484 inches

Base Thickness:

0.280 inches

End Application:

Ship, ohio class ssn (trident); signal distribution drawer assembly

Current Rating In Amps:

15.0

Mounting Facility Type And Quantity:

4 unthreaded hole

Terminal Connecting Link Quantity:

8 single

Nonfeedthru Terminal Type:

857 single

Terminal Connecting Link Type:

18 single

Nonfeedthru Terminal Quantity:

8 single

Terminal Pattern Arrangement:

Multi-row

Terminal Design:

Linked nonfeedthru

Product Name:

Terminal board, molded, barrier screw type, class 37tb; terminal block, military class, 8 position, 300 volts; kulka military class (a-a-59125)/(mil-t-55164) 37tb series

Special Features:

Board matl is gpt-30f, gray color, 130 deg. C; screws are brass nickel plate, 6-32 binder head, slotted, flammability rating: 94 v-o; wire size: no. 16-15 amps; supplied with end plates

Material:

Plastic board

Surface Treatment:

Nickel terminals

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A011b0