

View Online at <https://aerobasegroup.com/nsn/5940-01-527-7353>

Mounting Hole Diameter:

0.160 inches

Body Style:

Barrier type

Terminal Row Quantity:

2

Center To Center Distance Between Terminals:

0.380 inches

Distance Between Terminal Row Centers:

0.310 inches

Board Construction:

Solid construction

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.310 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

8.630 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.285 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.140 inches

Boardlength:

8.910 inches

Boardwidth:

0.880 inches

Boardheight:

0.440 inches

Board Height Excluding Terminals:

0.440 inches

Base Thickness:

0.280 inches

End Application:

Awg9 otps

Current Rating In Amps:

20.0

Mounting Facility Type And Quantity:

4 unthreaded hole

Nonfeedthru Terminal Type:

22 single

Nonfeedthru Terminal Quantity:

22 single

Terminal Pattern Arrangement:

Multi-row

Terminal Design:

Nonfeedthru

Product Name:

100 series kulka 670a gp series double row terminal block

Special Features:

Screws are no. 6-32 binder head, phil-slot; wire range: no. 12 - no. 22 awg - 20 amps; wire range with sems pressure screw no. 18 - no. 22 awg stranded copper wire only, 150 volts, 15 amps

Material:

Plastic phenolic board

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A011b0