

View Online at <https://aerobasegroup.com/nsn/5940-01-527-7353>

**Mounting Hole Diameter:**

0.160 inches

**Body Style:**

Barrier type

**Terminal Row Quantity:**

2

**Center To Center Distance Between Terminals:**

0.380 inches

**Distance Between Terminal Row Centers:**

0.310 inches

**Board Construction:**

Solid construction

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.310 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

8.630 inches

**Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:**

0.285 inches

**Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:**

0.140 inches

**Boardlength:**

8.910 inches

**Boardwidth:**

0.880 inches

**Boardheight:**

0.440 inches

**Board Height Excluding Terminals:**

0.440 inches

**Base Thickness:**

0.280 inches

**End Application:**

Awg9 otps

**Current Rating In Amps:**

20.0

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Nonfeedthru Terminal Type:**

22 single

**Nonfeedthru Terminal Quantity:**

22 single

**Terminal Pattern Arrangement:**

Multi-row

**Terminal Design:**

Nonfeedthru

**Product Name:**

100 series kulka 670a gp series double row terminal block

**Special Features:**

Screws are no. 6-32 binder head, phil-slot; wire range: no. 12 - no. 22 awg - 20 amps; wire range with sems pressure screw no. 18 - no. 22 awg stranded copper wire only, 150 volts, 15 amps

**Material:**

Plastic phenolic board

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A011b0