

View Online at <https://aerobasegroup.com/nsn/5940-01-528-4764>

Mounting Hole Diameter:

0.312 inches

Dielectric Withstanding Voltage In Volts:

600.0

Body Style:

Barrier type

Terminal Row Quantity:

2

Center To Center Distance Between Terminals:

0.500 inches

Distance Between Terminal Row Centers:

1.375 inches

Board Construction:

Solid construction

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.620 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.190 inches

Boardlength:

2.000 inches

Boardwidth:

2.000 inches

Boardheight:

1.190 inches

Board Height Excluding Terminals:

1.190 inches

Base Thickness:

0.380 inches

End Application:

Top assembly sect a - load center switchboard lc42, lpd-17

Current Rating In Amps:

75.0

Mounting Facility Type And Quantity:

4 unthreaded hole

Terminal Connecting Link Quantity:

2 single

Nonfeedthru Terminal Type:

857 single

Terminal Connecting Link Type:

12 single

Nonfeedthru Terminal Quantity:

4 single

Terminal Pattern Arrangement:

Multi-row

Terminal Design:

Linked nonfeedthru

Product Name:

Heavy duty terminal block, 1500 series

Special Features:

Short circuiting bar with nickel-plated brass insert, 4 shorting pins; wire range: no. 10 to 16 awg copper wire - 30 amps

Material:

Plastic phenolic board

Surface Treatment:

Nickel terminals

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A011b0