

View Online at <https://aerobasegroup.com/nsn/5940-01-528-4764>

**Mounting Hole Diameter:**

0.312 inches

**Dielectric Withstanding Voltage In Volts:**

600.0

**Body Style:**

Barrier type

**Terminal Row Quantity:**

2

**Center To Center Distance Between Terminals:**

0.500 inches

**Distance Between Terminal Row Centers:**

1.375 inches

**Board Construction:**

Solid construction

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.620 inches

**Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:**

0.190 inches

**Boardlength:**

2.000 inches

**Boardwidth:**

2.000 inches

**Boardheight:**

1.190 inches

**Board Height Excluding Terminals:**

1.190 inches

**Base Thickness:**

0.380 inches

**End Application:**

Top assembly sect a - load center switchboard lc42, lpd-17

**Current Rating In Amps:**

75.0

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Terminal Connecting Link Quantity:**

2 single

**Nonfeedthru Terminal Type:**

857 single

**Terminal Connecting Link Type:**

12 single

**Nonfeedthru Terminal Quantity:**

4 single

**Terminal Pattern Arrangement:**

Multi-row

**Terminal Design:**

Linked nonfeedthru

**Product Name:**

Heavy duty terminal block, 1500 series

**Special Features:**

Short circuiting bar with nickel-plated brass insert, 4 shorting pins; wire range: no. 10 to 16 awg copper wire - 30 amps

**Material:**

Plastic phenolic board

**Surface Treatment:**

Nickel terminals

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A011b0