

View Online at <https://aerobasegroup.com/nsn/5940-01-530-0520>

**Mounting Hole Diameter:**

0.203 inches

**Dielectric Withstanding Voltage In Volts:**

4000.0

**Body Style:**

Barrier type

**Terminal Row Quantity:**

2

**Center To Center Distance Between Terminals:**

0.560 inches

**Distance Between Terminal Row Centers:**

0.500 inches

**Board Construction:**

Hollow construction without insulated strip

**Terminal Facility Quantity:**

24

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.250 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.500 inches

**Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:**

0.405 inches

**Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:**

0.210 inches

**Boardlength:**

2.660 inches

**Boardwidth:**

1.310 inches

**Boardheight:**

0.710 inches

**Board Height Excluding Terminals:**

0.710 inches

**Base Thickness:**

0.450 inches

**End Application:**

Nsn 6115-01-454-6413; generator set, diesel engine

**Current Rating In Amps:**

30.0

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Terminal Connecting Link Quantity:**

6 single

**Nonfeedthru Terminal Type:**

857 single

**Terminal Connecting Link Type:**

16 single

**Nonfeedthru Terminal Quantity:**

24 single

**Terminal Pattern Arrangement:**

Multi-row

**Terminal Design:**

Linked nonfeedthru

**Special Features:**

Double row terminal blocks, 300 series, kulka 672 gp series; terminals, plated brass

**Material:**

Copper alloy terminals and nickel alloy terminals

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A011b0