

View Online at <https://aerobasegroup.com/nsn/5940-01-530-0520>

Mounting Hole Diameter:

0.203 inches

Dielectric Withstanding Voltage In Volts:

4000.0

Body Style:

Barrier type

Terminal Row Quantity:

2

Center To Center Distance Between Terminals:

0.560 inches

Distance Between Terminal Row Centers:

0.500 inches

Board Construction:

Hollow construction without insulated strip

Terminal Facility Quantity:

24

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.500 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.405 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.210 inches

Boardlength:

2.660 inches

Boardwidth:

1.310 inches

Boardheight:

0.710 inches

Board Height Excluding Terminals:

0.710 inches

Base Thickness:

0.450 inches

End Application:

Nsn 6115-01-454-6413; generator set, diesel engine

Current Rating In Amps:

30.0

Mounting Facility Type And Quantity:

4 unthreaded hole

Terminal Connecting Link Quantity:

6 single

Nonfeedthru Terminal Type:

857 single

Terminal Connecting Link Type:

16 single

Nonfeedthru Terminal Quantity:

24 single

Terminal Pattern Arrangement:

Multi-row

Terminal Design:

Linked nonfeedthru

Special Features:

Double row terminal blocks, 300 series, kulka 672 gp series; terminals, plated brass

Material:

Copper alloy terminals and nickel alloy terminals

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A011b0