

View Online at <https://aerobasegroup.com/nsn/5940-01-530-3514>

Mounting Hole Diameter:

0.196 inches

Dielectric Withstanding Voltage In Volts:

3000.0

Body Style:

Barrier type

Terminal Row Quantity:

2

Center To Center Distance Between Terminals:

0.438 inches

Distance Between Terminal Row Centers:

0.421 inches

Board Construction:

Solid construction

Terminal Facility Quantity:

30

Center To Center Distance Between Mounting Facilities Parallel To Length:

7.016 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.421 inches

Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:

0.196 inches

Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:

0.156 inches

Boardlength:

7.344 inches

Boardwidth:

1.125 inches

Boardheight:

0.578 inches

Board Height Excluding Terminals:

0.391 inches

Base Thickness:

0.375 inches

End Application:

Nsn 5920-01-360-3853; test stand, engine, semitrailer mounted; w/s: guided missile, intercept

Current Rating In Amps:

20.0

Mounting Facility Type And Quantity:

4 unthreaded hole

Terminal Connecting Link Quantity:

15 single

Nonfeedthru Terminal Type:

457 single

Terminal Connecting Link Type:

111 single

Nonfeedthru Terminal Quantity:

15 single

Terminal Pattern Arrangement:

Multi-row

Terminal Design:

Linked nonfeedthru

Product Name:

Assembly, terminal board, thermocouple

Special Features:

Terminal boards, molded barrier screw type, class 38tb

Material:

Plastic diallyl phthalate board

Material Specification:

A-a-59125/2 federal specification all material responses board

Surface Treatment:

Nickel terminals or tin alloy terminals

Specification Data:

58536 - a-a-59125/2 government specification and 81349 - mil-t-55164/2 government specification

Specification Or Standard:

38tb15 reference number

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A011b0