

View Online at <https://aerobasegroup.com/nsn/5940-01-531-1921>

Mounting Hole Diameter:

0.200 inches

Dielectric Withstanding Voltage In Volts:

1000.0

Body Style:

Barrier type

Center To Center Distance Between Terminals:

0.440 inches

Board Construction:

Solid construction

Terminal Facility Quantity:

5

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.190 inches

Boardlength:

2.980 inches

Boardwidth:

0.650 inches

Boardheight:

0.640 inches

Board Height Excluding Terminals:

0.640 inches

Base Thickness:

0.260 inches

Current Rating In Amps:

30.0

Mounting Facility Type And Quantity:

2 unthreaded hole

Terminal Pattern Arrangement:

Single row

Special Features:

Filtered; straight lead terminals; 150vac, 250vdc; wire size: no. 10-22 awg; screw size: no. 8-32; torque rating: 15 in-lb max; operating temp: m55 degrees c to p105 degrees c; capacitance: 1000 pf to 5000 pf; dielectric withstanding voltage: 1000 vac; 1700vdc; dc resistance: 0.01 ohms max; filter element provides high insertion loss for emi/rfi filtering of ac and dc power and control lines

Material:

Plastic board

Surface Treatment:

Tin terminals

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A011b0