

View Online at <https://aerobasegroup.com/nsn/5940-01-531-1921>

**Mounting Hole Diameter:**

0.200 inches

**Dielectric Withstanding Voltage In Volts:**

1000.0

**Body Style:**

Barrier type

**Center To Center Distance Between Terminals:**

0.440 inches

**Board Construction:**

Solid construction

**Terminal Facility Quantity:**

5

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.190 inches

**Boardlength:**

2.980 inches

**Boardwidth:**

0.650 inches

**Boardheight:**

0.640 inches

**Board Height Excluding Terminals:**

0.640 inches

**Base Thickness:**

0.260 inches

**Current Rating In Amps:**

30.0

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Terminal Pattern Arrangement:**

Single row

**Special Features:**

Filtered; straight lead terminals; 150vac, 250vdc; wire size: no. 10-22 awg; screw size: no. 8-32; torque rating: 15 in-lb max; operating temp: m55 degrees c to p105 degrees c; capacitance: 1000 pf to 5000 pf; dielectric withstanding voltage: 1000 vac; 1700vdc; dc resistance: 0.01 ohms max; filter element provides high insertion loss for emi/rfi filtering of ac and dc power and control lines

**Material:**

Plastic board

**Surface Treatment:**

Tin terminals

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A011b0