

View Online at <https://aerobasegroup.com/nsn/5940-01-535-4163>

**Mounting Hole Diameter:**

0.196 inches

**Dielectric Withstanding Voltage In Volts:**

3400.0

**Body Style:**

Barrier type

**Terminal Row Quantity:**

2

**Center To Center Distance Between Terminals:**

0.438 inches

**Distance Between Terminal Row Centers:**

0.421 inches

**Board Construction:**

Hollow construction without insulated strip

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.312 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.421 inches

**Distance From Bottom Edge Of Terminal Board To Center Of Mounting Hole:**

0.196 inches

**Distance From Left Edge Of Terminal Board To Center Of First Mounting Facility:**

0.156 inches

**Boardlength:**

1.641 inches

**Boardwidth:**

1.125 inches

**Boardheight:**

0.562 inches

**Board Height Excluding Terminals:**

0.562 inches

**Base Thickness:**

0.375 inches

**End Application:**

Controller, divers davit 241246 rev b sheet 2

**Current Rating In Amps:**

20.0

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Terminal Connecting Link Quantity:**

2 single

**Nonfeedthru Terminal Type:**

857 single

**Terminal Connecting Link Type:**

1 single

**Nonfeedthru Terminal Quantity:**

2 single

**Terminal Pattern Arrangement:**

Multi-row

**Terminal Design:**

Linked nonfeedthru

**Special Features:**

Numerals marked both above and below contact area w/ terminal board only

**Material:**

Plastic diallyl phthalate board and glass fiber board

**Material Specification:**

Mil-p-19833, type gdi-30f military specification single material response board

**Surface Treatment:**

Nickel terminals

**Specification Data:**

58536 - aa59125/2-38tb2b government specification

**Specification Or Standard:**

A-a-59125/2 reference number

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A011b0

**Mil-std (military Standard):**

Mil-p-19833 spec.