

View Online at <https://aerobasegroup.com/nsn/5940-01-573-0537>

Mounting Hole Diameter:

0.180 inches

Dielectric Withstanding Voltage In Volts:

300.0

Body Style:

Barrier type

Terminal Row Quantity:

2

Center To Center Distance Between Terminals:

0.440 inches

Distance Between Terminal Row Centers:

0.420 inches

Board Construction:

Hollow construction without insulated strip

Boardlength:

1.625 inches

Boardwidth:

1.130 inches

Boardheight:

0.500 inches

Board Height Excluding Terminals:

0.500 inches

Base Thickness:

0.310 inches

End Application:

Navy code 000a6573

Mounting Facility Type And Quantity:

4 unthreaded hole

Feedthru Connection End Type:

857 both ends first combination

Feedthru Terminal Quantity:

2 first combination

Terminal Pattern Arrangement:

Multi-row

Terminal Design:

Feedthru

Product Name:

Double row terminal block, kulka 601/801 gp series

Special Features:

Terminal matl is general purpose phenolic, 150 degrees c; terminal screws are 0.138-32 binder head, phil-slot, brass; wire range at no.12 to no.18 awg

Material:

Plastic phenolic board

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A011b0