

View Online at <https://aerobasegroup.com/nsn/5940-01-573-0537>

**Mounting Hole Diameter:**

0.180 inches

**Dielectric Withstanding Voltage In Volts:**

300.0

**Body Style:**

Barrier type

**Terminal Row Quantity:**

2

**Center To Center Distance Between Terminals:**

0.440 inches

**Distance Between Terminal Row Centers:**

0.420 inches

**Board Construction:**

Hollow construction without insulated strip

**Boardlength:**

1.625 inches

**Boardwidth:**

1.130 inches

**Boardheight:**

0.500 inches

**Board Height Excluding Terminals:**

0.500 inches

**Base Thickness:**

0.310 inches

**End Application:**

Navy code 000a6573

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Feedthru Connection End Type:**

857 both ends first combination

**Feedthru Terminal Quantity:**

2 first combination

**Terminal Pattern Arrangement:**

Multi-row

**Terminal Design:**

Feedthru

**Product Name:**

Double row terminal block, kulka 601/801 gp series

**Special Features:**

Terminal matl is general purpose phenolic, 150 degrees c; terminal screws are 0.138-32 binder head, phil-slot, brass; wire range at no.12 to no.18 awg

**Material:**

Plastic phenolic board

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A011b0