

View Online at <https://aerobasegroup.com/nsn/5940-01-587-1283>

**Dielectric Withstanding Voltage In Volts:**

3000.0

**Body Style:**

Pressure-contact-rigid

**Terminal Row Quantity:**

2

**Center To Center Distance Between Terminals:**

0.375 inches

**Distance Between Terminal Row Centers:**

0.312 inches

**Board Construction:**

Solid construction

**Boardlength:**

1.422 inches

**End Application:**

2350-01-087-1095, tank, combat, full tracked

**Current Rating In Amps:**

15.0

**Mounting Facility Type And Quantity:**

2 clip

**Terminal Pattern Arrangement:**

Multi-row

**Product Name:**

Terminal board, molded, barrier, screw type, class 37tb

**Special Features:**

Two rows of 4 terminals each; centerline between 1st and 4th terminal each row is 1.125 inches nom; screw thread within terminal nbr 6-32unc-2a; voltage rating maximum 300 volts; specific plastic material is gpt-30f; max temp 130 degrees c; board height 0.484 inches nom; board width 0.875 inches nom

**Material:**

Plastic board

**Material Specification:**

Mil-m-4519 military specification single material response board

**Specification Data:**

81349-mil-t-55164/1e, 28 jan 87 superceded by a-a-59125/1 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A011b0

**Mil-std (military Standard):**

Mil-m-4519 spec.