

View Online at <https://aerobasegroup.com/nsn/5945-00-004-6292>

Thread Class:

2a second mounting facility

Thread Direction:

Right-hand second mounting facility

Thread Length:

0.375 inches second mounting facility

Overall Length:

1.109 inches

Overall Height:

2.053 inches

Overall Width:

0.859 inches

Case Material:

Plastic

Environmental Protection:

Dustproof

Fragility Factor:

Moderately rugged

Contact Material:

Silver

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

650.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

1 threaded stud second mounting facility

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

48 first mounting facility

Thread Size:

0.138 inches second mounting facility

Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

Time Delay:

0.013 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

24.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

3.0 amperes ac resistive load and 3.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

120.0 ac and 30.0 dc

Energizing Element Power Rating:

900.0 milliwatts

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Thread Series Designator:

Unc second mounting facility

Terminal Type And Quantity:

14 tab, solder lug all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A03300