## NSN 5945-00-009-1239

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-009-1239

Overall Length:
1.750 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.396 inches single mounting facility and 1.446 inches single mounting facility
Overall Height:
1.270 inches
Overall Width:
1.015 inches
Mounting Slot Width:
0.150 inches single mounting facility
Case Material:
Metal
Environmental Protection:
Hermetic
Fragility Factor:
Moderately rugged
Contact Material:
Silver
Contact Surface Treatment:
Gold
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
29.0 ohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
3 slotted hole single mounting facility
Storage Type:
General purpose warehouse
Features Provided:
Polarized
Cubic Measure:
2.256 cubic inches

Mounting Facility Pattern:
Triangle single mounting facility

## NSN 5945-00-009-1239

Electromagnetic Relay - Page 2 of 2



## **Nonpile-up Main Contact Arrangement:**

4 pole, double throw, one position momentary

## **Operating Current Rating And Type:**

120.0 milliamperes dc single winding

Time Delay:

0.015 seconds fixed operate and release time

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

0.625 inches single mounting facility

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

15.0 amperes ac resistive load and 15.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

**Precious Material And Location:** 

Contact surfaces gold and contacts silver

**Precious Material:** 

Gold and silver

**Terminal Type And Quantity:** 

14 pin all functions

Shelf Life:

N/a

**Unit Of Measure:** 

\_

**Demilitarization:** 

No

Fiig:

A03300