# NSN 5945-00-009-3037

Electromagnetic Relay - Page 1 of 2

1.067 inches single mounting facility

Overall Length: 1.453 inches



View Online at https://aerobasegroup.com/nsn/5945-00-009-3037

**Center To Center Distance Between Mounting Facilities Parallel To Length:** 

Overall Height:
1.491 inches
Overall Width:
0.410 inches
Case Material:
Metal
Environmental Protection:
Hermetic
<b>Unthreaded Mounting Hole Diameter:</b>
0.120 inches single mounting facility
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
10.0 kilohms single winding and 9.0 kilohms single winding
Duty Type:
Continuous
Arc Quenching Method:
Air
Mounting Facility Type And Quantity:
2 unthreaded hole single mounting facility
Storage Type:
General purpose warehouse
Cubic Measure:
0.888 cubic inches
Mounting Facility Pattern:
In-line single mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Operating Current Rating And Type:
4.0 milliamperes dc single winding
Time Delay:

0.015 seconds fixed operate time

## NSN 5945-00-009-3037

Electromagnetic Relay - Page 2 of 2



### Main Contact Load Current Rating At Maximum Rated Voltage:

100.0 milliamperes dc lamp load

### Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

#### **Test Data Document:**

81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Terminal Type And Quantity:**

8 pin all functions

#### **Specification Data:**

81349-mil-r-5757/13 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A03300