NSN 5945-00-009-3116

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-009-3116

Overall I	Length:
-----------	---------

0.890 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.700 inches single mounting facility

Overall Height:

0.235 inches

Overall Width:

0.500 inches

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.120 inches single mounting facility

Fragility Factor:

Moderately rugged

Winding Quantity:

1

Purpose For Which Designed:

General

Coil Quantity:

Winding Dc Resistance Rating:

1.5 kilohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Mounting Facility Pattern:

In-line single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Time Delay:

0.006 seconds fixed operate and release time

Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

28.0 dc

Test Data Document:

81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5945-00-009-3116

Electromagnetic Relay - Page 2 of 2



Terminal Type And Quantity:
8 pin all functions
Specification Data:
81349-mil-r-5757/19 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A03300