NSN 5945-00-010-1109

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-010-1109

| · |
|---|
| Overall Length: |
| 1.670 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.060 inches single mounting facility |
| Overall Height: |
| 0.730 inches |
| Overall Width: |
| 1.080 inches |
| Environmental Protection: |
| Hermetic |
| Unthreaded Mounting Hole Diameter: |
| 0.125 inches single mounting facility |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 2.5 kilohms single winding |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 2 unthreaded hole single mounting facility |
| Mounting Facility Pattern: |
| In-line single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 2 pole, double throw, one position momentary, two positions maintained |
| Operating Current Rating And Type: |
| 11.0 milliamperes dc single winding |
| Time Delay: |
| 0.005 seconds fixed release time |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 55.0 volts dc 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 2.0 amperes ac inductive load and 2.0 amperes dc inductive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 115.0 ac and 32.0 dc |
| Terminal Type And Quantity: |
| 8 pin all functions |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5945-00-010-1109

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300