## NSN 5945-00-025-7232

Reed Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-025-7232

#### **Overall Length:**

- 1.300 inches
- **Overall Height:**
- 0.500 inches

#### **Overall Width:**

0.500 inches

#### **Environmental Protection:**

Dust tight

#### Fragility Factor:

Moderately rugged

## Winding Quantity:

1

#### **Purpose For Which Designed:**

General

#### **Coil Quantity:**

1

#### Winding Dc Resistance Rating:

420.0 ohms single winding

## Duty Type:

Continuous

#### Mounting Facility Type And Quantity:

1 printed circuit terminal single mounting facility

#### Storage Type:

General purpose warehouse

#### Nonpile-up Main Contact Arrangement:

1 pole, double throw, one position momentary

#### **Operating Voltage Rating And Type At Specificationified Temp:**

12.0 volts dc 25 degrees celsius single winding

#### Main Contact Load Current Rating At Maximum Rated Voltage:

500.0 milliamperes dc resistive load

#### Main Contact Maximum Voltage Rating In Volts:

28.0 dc

## **Test Data Document:**

81349-mil-r-5757 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Terminal Type And Quantity:

3 pin contacts

## Specification Data:

81349-mil-r-5757/29 government specification

## Shelf Life:

N/a

- Unit Of Measure:
- ---

# NSN 5945-00-025-7232

Reed Relay - Page 2 of 2

Demilitarization:

No

Fiig:

A03300

