NSN 5945-00-034-3898

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-034-3898

| Overall Length: |
|---|
| 2.590 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.000 inches single mounting facility |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.500 inches single mounting facility |
| Overall Height: |
| 3.590 inches |
| Overall Width: |
| 3.060 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.196 inches single mounting facility |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole single mounting facility |
| Features Provided: |
| Coil voltage suppression |
| Mounting Facility Pattern: |
| Rectangular single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 1 pole, double throw, one position momentary |
| Operating Current Rating And Type: |
| 2.0 milliamperes ac single winding |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 115.0 volts ac 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 5.0 amperes dc resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 28.0 dc |
| Terminal Type And Quantity: |
| 5 screw all functions |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5945-00-034-3898

Electromagnetic Relay - Page 2 of 2



Fiig:

A03300