NSN 5945-00-050-8468

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-050-8468

3
Thread Class:
2a single mounting facility
Thread Direction:
Right-hand single mounting facility
Overall Length:
Between 1.391 inches and 1.422 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.495 inches single mounting facility and 0.505 inches single mounting facility
Overall Height:
Between 1.750 inches and 1.781 inches
Overall Width:
Between 0.859 inches and 0.891 inches
Case Material:
Metal
Environmental Protection:
Dustproof
Fragility Factor:
Moderately rugged
Winding Quantity:
1
Purpose For Which Designed:
General
Coil Quantity:
1
Winding Dc Resistance Rating:
365.0 ohms single winding
Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

1 threaded stud single mounting facility

Pile-up Main Contact Form Arrangement:

1c and 2a

Storage Type:

General purpose warehouse

Cubic Measure:

2.256 cubic inches

Thready Qty Per Inch (tpi):

40 single mounting facility

Thread Size:

0.112 inches single mounting facility

NSN 5945-00-050-8468

Electromagnetic Relay - Page 2 of 2

Fiig: A03300



Mounting Facility Pattern:
Triangle single mounting facility
Time Delay:
0.015 seconds fixed operate time
Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:
1.000 inches single mounting facility
Operating Voltage Rating And Type At Specificationified Temp:
28.0 volts dc 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
4.0 amperes ac resistive load
Main Contact Maximum Voltage Rating In Volts:
115.0 ac
Thread Series Designator:
Unc single mounting facility
Terminal Type And Quantity:
9 wire hook all functions
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No