NSN 5945-00-052-0658

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-052-0658

| Overall Length: |
|---|
| 6.562 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 6.052 inches single mounting facility and 6.072 inches single mounting facility |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.031 inches single mounting facility |
| Overall Height: |
| 3.375 inches |
| Overall Width: |
| 2.812 inches |
| Case Material: |
| Metal |
| Environmental Protection: |
| Corrosion resistant |
| Unthreaded Mounting Hole Diameter: |
| 0.191 inches single mounting facility and 0.206 inches single mounting facility |
| Fragility Factor: |
| Moderately rugged |
| Winding Quantity: |
| 1 |
| Purpose For Which Designed: |
| General |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 130.0 ohms single winding |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole single mounting facility |
| Storage Type: |
| General purpose warehouse |
| Cubic Measure: |
| 62.278 cubic inches |
| Mounting Facility Pattern: |
| Rectangular single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 2 pole, single throw, normally open, momentary action and 1 pole, single throw, normally closed, momentary action |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 28.0 volts dc 25 degrees celsius single winding |

5.0 amperes dc inductive load

Main Contact Load Current Rating At Maximum Rated Voltage:

NSN 5945-00-052-0658

Electromagnetic Relay - Page 2 of 2



Fiig: A03300