NSN 5945-00-052-4177

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-052-4177

Overall Length:

Between 1.208 inches and 1.218 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.995 inches single mounting facility and 1.005 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.120 inches single mounting facility and 0.130 inches single mounting facility

Overall Height:

Between 0.880 inches and 0.890 inches

Overall Width:

Between 0.390 inches and 0.400 inches

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.094 inches single mounting facility and 0.102 inches single mounting facility

Fragility Factor:

Moderately rugged

Winding Quantity:

•

Purpose For Which Designed:

General

Coil Quantity:

_

Winding Dc Resistance Rating:

1.92 kilohms single winding

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

2 unthreaded hole single mounting facility

Pile-up Main Contact Form Arrangement:

2с

Storage Type:

General purpose warehouse

Cubic Measure:

0.434 cubic inches

Mounting Facility Pattern:

Diagonal single mounting facility

Time Delay:

0.01 seconds fixed operate time

Operating Voltage Rating And Type At Specificationified Temp:

50.0 volts dc 25 degrees celsius single winding

NSN 5945-00-052-4177

Electromagnetic Relay - Page 2 of 2



Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac resistive load and 1.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 50.0 dc

Terminal Type And Quantity:

8 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300