NSN 5945-00-052-8058

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-052-8058

| Overall Le | ength: |
|------------|--------|
|------------|--------|

1.410 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.195 inches single mounting facility and 1.205 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.395 inches single mounting facility and 0.405 inches single mounting facility

Overall Height:

0.990 inches

Overall Width:

0.600 inches

Environmental Protection:

Hermetic

Unthreaded Mounting Hole Diameter:

0.091 inches single mounting facility and 0.101 inches single mounting facility

Fragility Factor:

Moderately rugged

Winding Quantity:

Purpose For Which Designed:

General

Coil Quantity:

1

Winding Dc Resistance Rating:

500.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Storage Type:

General purpose warehouse

Features Provided:

Polarized

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

4 pole, double throw, one position momentary

Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

28.0 dc

NSN 5945-00-052-8058

Electromagnetic Relay - Page 2 of 2



| Terminal Type And Quantity | Type And Quantity | T | erminal | Т |
|----------------------------|-------------------|---|---------|---|
|----------------------------|-------------------|---|---------|---|

14 pin all functions

Fsc Application Data (non-core):

Relay, armature, except engine

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300