NSN 5945-00-056-4932

Electrical Solenoid - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-056-4932

| Center To Center Distance Between Mounting Facilities Parallel To Length: |
|---|
| 0.500 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.438 inches |
| Case Material: |
| Steel |
| Case Surface Treatment: |
| Zinc |
| Environmental Protection: |
| Any acceptable |
| Inclosure Type: |
| Fully enclosed |
| Magnetic Coil Quantity: |
| 1 |
| Electrical Resistance: |
| 291.00 ohms |
| Voltage Rating In Volts: |
| 110.0 ac |
| Mounting Facility Type And Quantity: |
| 2 threaded hole |
| Actuator Stroke Type: |
| Pull |
| Linear Force Delivered: |
| 1.40 pounds |
| Power Takeoff Connection Type: |
| Clevis tongue |
| Energizing Stroke Maximum Length: |
| 0.312 inches |
| Thread Size: |
| 0.138 inches mounting facility hole |
| Mounting Facility Pattern: |
| Two position diagonal |
| Thread Series Designator: |
| Unc mounting facility hole |
| Terminal Type And Quantity: |
| 4 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5945-00-056-4932 Electrical Solenoid - Page 2 of 2



Fiig:

A134a0