## NSN 5945-00-056-9872

Electromagnetic Relay - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5945-00-056-9872

Overall Length:         0.390 inches         Overall Height:         0.530 inches         Overall Width:         0.190 inches         Environmental Protection:         Hermetic         Winding Quantity:         1         Coil Quantity:         1         Winding Dc Resistance Rating:         2.0 kilohms single winding         Duty Type:         Continuous         Mounting Facility Type And Quantity:         1 terminal single mounting facility         Nonpile-up Main Contact Arrangement:         1 pole, double throw, one position momentary         Operating Current Rating And Type:         7.0 milliamperes dc single winding         Operating Voltage Rating And Type At Specificationified Temp         26.5 volts dc 25 degrees celsius single winding         Operating Voltage Rating And Type At Specificationified Temp         26.5 volts dc 25 degrees celsius single winding         Main Contact Load Current Rating At Maximum Rated Voltage:         28.0 dc         Terminal Type And Quantity:         5 pin all functions         Shelf Life:         N/a         Unit Of Measure:         -         Demilitarization: </th <th>ew Online at https://aerobasegroup.com/nsn/5945-00-056-9872</th>	ew Online at https://aerobasegroup.com/nsn/5945-00-056-9872
Overall Height: 0.530 inches Overall Width: 0.190 inches Environmental Protection: Hermetic Winding Quantity: 1 Coil Quantity: 1 Winding Dc Resistance Rating: 2.0 kilohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 terminal single mounting facility Nonpile-up Main Contact Arrangement: 1 pole, double throw, one position momentary Operating Current Rating And Type: 7.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 250.0 milliamperes dc inductive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc Terminal Type And Quantity: 5 pin all functions Shelf Life: N/a Unit Of Measure:  Demilitarization: No	verall Length:
0.530 inches Overall Width: 0.190 inches Environmental Protection: Hermetic Winding Quantity: 1 Coil Quantity: 1 Winding Dc Resistance Rating: 2.0 kilohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 terminal single mounting facility Nonpile-up Main Contact Arrangement: 1 pole, double throw, one position momentary Operating Current Rating And Type: 7.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 250.0 milliamperes dc inductive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc Terminal Type And Quantity: 5 pin all functions Shelf Life: N/a Unit Of Measure:  Demilitarization: No	390 inches
Overall Width: 0.190 inches Environmental Protection: Hermetic Winding Quantity: 1 Coil Quantity: 1 Winding Dc Resistance Rating: 2.0 kilohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 terminal single mounting facility Nonpile-up Main Contact Arrangement: 1 pole, double throw, one position momentary Operating Current Rating And Type: 7.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 250.0 milliamperes dc inductive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc Terminal Type And Quantity: 5 pin all functions Shelf Life: N/a Unit Of Measure:  Demilitarization: No	verall Height:
0.190 inches Environmental Protection: Hermetic Winding Quantity: 1 Coil Quantity: 1 Winding Dc Resistance Rating: 2.0 kilohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 terminal single mounting facility Nonpile-up Main Contact Arrangement: 1 pole, double throw, one position momentary Operating Current Rating And Type: 7.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 250.0 milliamperes dc inductive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc Terminal Type And Quantity: 5 pin all functions Shelf Life: N/a Unit Of Measure:  Demilitarization: No	530 inches
Environmental Protection: Hermetic Winding Quantity: 1 Coil Quantity: 1 Winding Dc Resistance Rating: 2.0 kilohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 terminal single mounting facility Nonpile-up Main Contact Arrangement: 1 pole, double throw, one position momentary Operating Current Rating And Type: 7.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 250.0 milliamperes dc inductive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc Terminal Type And Quantity: 5 pin all functions Shelf Life: N/a Unit Of Measure:  Demilitarization: No	verall Width:
Hermetic Hermetic Winding Quantity: I Coil Quantity: I Vinding Dc Resistance Rating: 2.0 kilohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: I terminal single mounting facility Nonpile-up Main Contact Arrangement: I pole, double throw, one position momentary Operating Current Rating And Type: 7.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 250.0 milliamperes dc inductive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc Terminal Type And Quantity: 5 pin all functions Shelf Life: N/a Unit Of Measure: Demilitarization: No	190 inches
Winding Quantity:          1         Coil Quantity:         1         Winding Dc Resistance Rating:         2.0 kilohms single winding         Duty Type:         Continuous         Mounting Facility Type And Quantity:         1 terminal single mounting facility         Nonpile-up Main Contact Arrangement:         1 pole, double throw, one position momentary         Operating Current Rating And Type:         7.0 milliamperes dc single winding         Operating Voltage Rating And Type At Specificationified Temp         26.5 volts dc 25 degrees celsius single winding         Main Contact Load Current Rating At Maximum Rated Voltage:         250.0 milliamperes dc inductive load         Main Contact Maximum Voltage Rating In Volts:         28.0 dc         Terminal Type And Quantity:         5 pin all functions         Shelf Life:         N/a         Unit Of Measure:            Demilitarization:         No	nvironmental Protection:
1         Coil Quantity:         1         Winding Dc Resistance Rating:         2.0 kilohms single winding         Duty Type:         Continuous         Mounting Facility Type And Quantity:         1 terminal single mounting facility         Nonpile-up Main Contact Arrangement:         1 pole, double throw, one position momentary         Operating Current Rating And Type:         7.0 milliamperes dc single winding         Operating Voltage Rating And Type At Specificationified Temp         26.5 volts dc 25 degrees celsius single winding         Main Contact Load Current Rating At Maximum Rated Voltage:         250.0 milliamperes dc inductive load         Main Contact Maximum Voltage Rating In Volts:         28.0 dc         Terminal Type And Quantity:         5 pin all functions         Shelf Life:         N/a         Unit Of Measure:            Demilitarization:         No	ermetic
Coil Quantity: 1  Winding Dc Resistance Rating: 2.0 kilohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 terminal single mounting facility Nonpile-up Main Contact Arrangement: 1 pole, double throw, one position momentary Operating Current Rating And Type: 7.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 250.0 milliamperes dc inductive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc Terminal Type And Quantity: 5 pin all functions Shelf Life: N/a Unit Of Measure: Demilitarization: No	inding Quantity:
1         Winding Dc Resistance Rating:         2.0 kilohms single winding         Duty Type:         Continuous         Mounting Facility Type And Quantity:         1 terminal single mounting facility         Nonpile-up Main Contact Arrangement:         1 pole, double throw, one position momentary         Operating Current Rating And Type:         7.0 milliamperes dc single winding         Operating Voltage Rating And Type At Specificationified Temp         26.5 volts dc 25 degrees celsius single winding         Main Contact Load Current Rating At Maximum Rated Voltage:         250.0 milliamperes dc inductive load         Main Contact Maximum Voltage Rating In Volts:         28.0 dc         Terminal Type And Quantity:         5 pin all functions         Shelf Life:         N/a         Unit Of Measure:            Demilitarization:         No	
Winding Dc Resistance Rating: 2.0 kilohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 terminal single mounting facility Nonpile-up Main Contact Arrangement: 1 pole, double throw, one position momentary Operating Current Rating And Type: 7.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 250.0 milliamperes dc inductive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc Terminal Type And Quantity: 5 pin all functions Shelf Life: N/a Unit Of Measure: Demilitarization: No	oil Quantity:
2.0 kilohms single winding Duty Type: Continuous Mounting Facility Type And Quantity: 1 terminal single mounting facility Nonpile-up Main Contact Arrangement: 1 pole, double throw, one position momentary Operating Current Rating And Type: 7.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 250.0 milliamperes dc inductive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc Terminal Type And Quantity: 5 pin all functions Shelf Life: N/a Unit Of Measure:  Demilitarization: No	
Duty Type: Continuous Mounting Facility Type And Quantity: 1 terminal single mounting facility Nonpile-up Main Contact Arrangement: 1 pole, double throw, one position momentary Operating Current Rating And Type: 7.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 250.0 milliamperes dc inductive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc Terminal Type And Quantity: 5 pin all functions Shelf Life: N/a Unit Of Measure:  Demilitarization: No	inding Dc Resistance Rating:
Continuous Mounting Facility Type And Quantity: 1 terminal single mounting facility Nonpile-up Main Contact Arrangement: 1 pole, double throw, one position momentary Operating Current Rating And Type: 7.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 250.0 milliamperes dc inductive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc Terminal Type And Quantity: 5 pin all functions Shelf Life: N/a Unit Of Measure:  Demilitarization: No	0 kilohms single winding
Mounting Facility Type And Quantity: 1 terminal single mounting facility Nonpile-up Main Contact Arrangement: 1 pole, double throw, one position momentary Operating Current Rating And Type: 7.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 250.0 milliamperes dc inductive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc Terminal Type And Quantity: 5 pin all functions Shelf Life: N/a Unit Of Measure:  Demilitarization: No	uty Type:
1 terminal single mounting facility Nonpile-up Main Contact Arrangement: 1 pole, double throw, one position momentary Operating Current Rating And Type: 7.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 250.0 milliamperes dc inductive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc Terminal Type And Quantity: 5 pin all functions Shelf Life: N/a Unit Of Measure:  Demilitarization: No	ontinuous
Nonpile-up Main Contact Arrangement: 1 pole, double throw, one position momentary Operating Current Rating And Type: 7.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 250.0 milliamperes dc inductive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc Terminal Type And Quantity: 5 pin all functions Shelf Life: N/a Unit Of Measure:  Demilitarization: No	ounting Facility Type And Quantity:
1 pole, double throw, one position momentary Operating Current Rating And Type: 7.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 250.0 milliamperes dc inductive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc Terminal Type And Quantity: 5 pin all functions Shelf Life: N/a Unit Of Measure:  Demilitarization: No	terminal single mounting facility
Operating Current Rating And Type: 7.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 250.0 milliamperes dc inductive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc Terminal Type And Quantity: 5 pin all functions Shelf Life: N/a Unit Of Measure:  Demilitarization: No	onpile-up Main Contact Arrangement:
7.0 milliamperes dc single winding Operating Voltage Rating And Type At Specificationified Temp 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 250.0 milliamperes dc inductive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc Terminal Type And Quantity: 5 pin all functions Shelf Life: N/a Unit Of Measure:  Demilitarization: No	pole, double throw, one position momentary
Operating Voltage Rating And Type At Specificationified Temp 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 250.0 milliamperes dc inductive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc Terminal Type And Quantity: 5 pin all functions Shelf Life: N/a Unit Of Measure:  Demilitarization: No	perating Current Rating And Type:
26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage: 250.0 milliamperes dc inductive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc Terminal Type And Quantity: 5 pin all functions Shelf Life: N/a Unit Of Measure:  Demilitarization: No	0 milliamperes dc single winding
Main Contact Load Current Rating At Maximum Rated Voltage: 250.0 milliamperes dc inductive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc Terminal Type And Quantity: 5 pin all functions Shelf Life: N/a Unit Of Measure:  Demilitarization: No	perating Voltage Rating And Type At Specificationified Temp
250.0 milliamperes dc inductive load Main Contact Maximum Voltage Rating In Volts: 28.0 dc Terminal Type And Quantity: 5 pin all functions Shelf Life: N/a Unit Of Measure:  Demilitarization: No	3.5 volts dc 25 degrees celsius single winding
Main Contact Maximum Voltage Rating In Volts: 28.0 dc Terminal Type And Quantity: 5 pin all functions Shelf Life: N/a Unit Of Measure:  Demilitarization:	ain Contact Load Current Rating At Maximum Rated Voltage
28.0 dc Terminal Type And Quantity: 5 pin all functions Shelf Life: N/a Unit Of Measure:  Demilitarization: No	50.0 milliamperes dc inductive load
Terminal Type And Quantity: 5 pin all functions Shelf Life: N/a Unit Of Measure:  Demilitarization: No	ain Contact Maximum Voltage Rating In Volts:
5 pin all functions Shelf Life: N/a Unit Of Measure:  Demilitarization: No	3.0 dc
Shelf Life: N/a Unit Of Measure:  Demilitarization: No	erminal Type And Quantity:
N/a Unit Of Measure:  Demilitarization: No	pin all functions
Unit Of Measure:  Demilitarization: No	helf Life:
 Demilitarization: No	/a
No	nit Of Measure:
No	
	emilitarization:
	0
Fiig:	ig:
A03300	03300