

View Online at <https://aerobasegroup.com/nsn/5945-00-057-0668>

Thread Class:

2a single mounting facility

Overall Length:

0.800 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.412 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.200 inches single mounting facility

Overall Height:

0.870 inches

Overall Width:

0.400 inches

Environmental Protection:

Hermetic

Winding Quantity:

1

Coil Quantity:

1

Winding Dc Resistance Rating:

750.0 ohms single winding

Duty Type:

Continuous

Mounting Facility Type And Quantity:

2 threaded stud single mounting facility

Features Provided:

Polarized

Thread Size:

0.112 inches single mounting facility

Mounting Facility Pattern:

Diagonal single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

Operating Voltage Rating And Type At Specificationified Temp:

26.5 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

2.00 amperes dc inductive load

Main Contact Maximum Voltage Rating In Volts:

32.0 dc

Thread Series Designator:

Unc single mounting facility

Terminal Type And Quantity:

8 pin all functions

Fsc Application Data (non-core):

Relay armature except engine

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300