

View Online at <https://aerobasegroup.com/nsn/5945-00-058-6710>

Overall Length:

6.320 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.000 inches single mounting facility

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.000 inches single mounting facility

Overall Height:

7.120 inches

Overall Width:

5.120 inches

Unthreaded Mounting Hole Diameter:

0.221 inches single mounting facility

Winding Quantity:

1

Coil Quantity:

2

Duty Type:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole single mounting facility

Mounting Facility Pattern:

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

3 pole, double throw, one position momentary

Nonpile-up Auxiliary Contact Arrangement:

10 pole, single throw, normally closed, momentary action and 2 pole, single throw, normally open, momentary action

Auxiliary Contact Maximum Voltage Rating In Volts:

208.0 ac

Operating Voltage Rating And Type At Specificationified Temp:

28.0 volts dc 25 degrees celsius single winding

Main Contact Load Current Rating At Maximum Rated Voltage:

250.0 amperes ac resistive load

Main Contact Maximum Voltage Rating In Volts:

208.0 ac

Terminal Type And Quantity:

37 pin all functions

Fsc Application Data (non-core):

Relay armature, except engine

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300