NSN 5945-00-059-4813

Electromagnetic Relay - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5945-00-059-4813 |
|---------------------------------------------------------------------------|
| Overall Length: |
| 1.170 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 0.125 inches single mounting facility |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.000 inches single mounting facility |
| Overall Height: |
| 0.870 inches |
| Overall Width: |
| 0.400 inches |
| Environmental Protection: |
| Hermetic |
| Unthreaded Mounting Hole Diameter: |
| 0.096 inches single mounting facility |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Winding Dc Resistance Rating: |
| 615.0 ohms single winding |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 4 unthreaded hole single mounting facility |
| Pile-up Main Contact Form Arrangement: |
| 2c |
| Features Provided: |
| Polarized |
| Mounting Facility Pattern: |
| Rectangular single mounting facility |
| Operating Current Rating And Type: |
| 40.0 milliamperes dc single winding |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 26.5 volts dc 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 1.0 amperes ac resistive load and 2.0 amperes dc resistive load |
| Main Contact Maximum Voltage Rating In Volts: |
| 115.0 ac and 29.0 dc |
| Terminal Type And Quantity: |
| 8 pin all functions |
| Shelf Life: |

N/a

NSN 5945-00-059-4813

Electromagnetic Relay - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A03300