## NSN 5945-00-060-2248

Electromagnetic Relay - Page 1 of 2

1.078 inches single mounting facility

Overall Length: 1.310 inches

Overall Height: 0.410 inches



View Online at https://aerobasegroup.com/nsn/5945-00-060-2248

**Center To Center Distance Between Mounting Facilities Parallel To Length:** 

26.5 volts dc 25 degrees celsius single winding	
Hermetic Unthreaded Mounting Hole Diameter: 0.096 inches single mounting facility Fragility Factor: Moderately rugged Winding Quantity: 1 Purpose For Which Designed: General Coil Quantity: 1 Winding Dc Resistance Rating: 765.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Storage Type: General purpose warehouse Features Provided: Polarized Cubic Measure: 0.317 cubic inches Mounting Facility Pattern: In-line single mounting facility Operating Voltage Rating And Type At Specificationified Temp 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage 100.0 milliamperes ac resistive load Main Contact Maximum Voltage Rating In Volts:	0.590 inches
Unthreaded Mounting Hole Diameter:  0.096 inches single mounting facility Fragility Factor: Moderately rugged Winding Quantity:  1 Purpose For Which Designed: General Coil Quantity:  1 Winding Dc Resistance Rating: 765.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Storage Type: General purpose warehouse Features Provided: Polarized Cubic Measure: 0.317 cubic inches Mounting Facility Pattern: In-line single mounting facility Operating Voltage Rating And Type At Specificationified Temp 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage 100.0 milliamperes ac resistive load Main Contact Maximum Voltage Rating In Volts:	Environmental Protection:
O.096 inches single mounting facility  Fragility Factor:  Moderately rugged  Winding Quantity:  1  Purpose For Which Designed: General  Coil Quantity:  1  Winding Dc Resistance Rating: 765.0 ohms single winding  Duty Type: Continuous  Arc Quenching Method: Air  Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility  Storage Type: General purpose warehouse  Features Provided: Polarized  Cubic Measure: 0.317 cubic inches  Mounting Facility Pattern: In-line single mounting facility  Operating Voltage Rating And Type At Specificationified Temp 26.5 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage 100.0 milliamperes ac resistive load  Main Contact Maximum Voltage Rating In Volts:	Hermetic
Fragility Factor: Moderately rugged Winding Quantity:  1 Purpose For Which Designed: General Coil Quantity:  1 Winding Dc Resistance Rating: 765.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Storage Type: General purpose warehouse Features Provided: Polarized Cubic Measure: 0.317 cubic inches Mounting Facility Pattern: In-line single mounting facility Operating Voltage Rating And Type At Specificationified Tem; 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage; 100.0 milliamperes ac resistive load Main Contact Maximum Voltage Rating In Volts:	Unthreaded Mounting Hole Diameter:
Moderately rugged Winding Quantity:  1 Purpose For Which Designed: General Coil Quantity:  1 Winding Dc Resistance Rating: 765.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Storage Type: General purpose warehouse Features Provided: Polarized Cubic Measure: 0.317 cubic inches Mounting Facility Pattern: In-line single mounting facility Operating Voltage Rating And Type At Specificationified Tem 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage 100.0 milliamperes ac resistive load Main Contact Maximum Voltage Rating In Volts:	0.096 inches single mounting facility
Winding Quantity:  Purpose For Which Designed: General Coil Quantity:  Winding Dc Resistance Rating: 765.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Storage Type: General purpose warehouse Features Provided: Polarized Cubic Measure: 0.317 cubic inches Mounting Facility Pattern: In-line single mounting facility Operating Voltage Rating And Type At Specificationified Tem 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage 100.0 milliamperes ac resistive load Main Contact Maximum Voltage Rating In Volts:	Fragility Factor:
Purpose For Which Designed: General Coil Quantity:  Winding Dc Resistance Rating: 765.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Storage Type: General purpose warehouse Features Provided: Polarized Cubic Measure: 0.317 cubic inches Mounting Facility Pattern: In-line single mounting facility Operating Voltage Rating And Type At Specificationified Tem 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage 100.0 milliamperes ac resistive load Main Contact Maximum Voltage Rating In Volts:	Moderately rugged
Purpose For Which Designed: General Coil Quantity:  1 Winding Dc Resistance Rating: 765.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Storage Type: General purpose warehouse Features Provided: Polarized Cubic Measure: 0.317 cubic inches Mounting Facility Pattern: In-line single mounting facility Operating Voltage Rating And Type At Specificationified Tem 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage 100.0 milliamperes ac resistive load Main Contact Maximum Voltage Rating In Volts:	Winding Quantity:
Coil Quantity:  1 Winding Dc Resistance Rating: 765.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Storage Type: General purpose warehouse Features Provided: Polarized Cubic Measure: 0.317 cubic inches Mounting Facility Pattern: In-line single mounting facility Operating Voltage Rating And Type At Specificationified Temp 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage 100.0 milliamperes ac resistive load Main Contact Maximum Voltage Rating In Volts:	1
Coil Quantity:  1 Winding Dc Resistance Rating: 765.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Storage Type: General purpose warehouse Features Provided: Polarized Cubic Measure: 0.317 cubic inches Mounting Facility Pattern: In-line single mounting facility Operating Voltage Rating And Type At Specificationified Temp 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage 100.0 milliamperes ac resistive load Main Contact Maximum Voltage Rating In Volts:	Purpose For Which Designed:
Winding Dc Resistance Rating: 765.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Storage Type: General purpose warehouse Features Provided: Polarized Cubic Measure: 0.317 cubic inches Mounting Facility Pattern: In-line single mounting facility Operating Voltage Rating And Type At Specificationified Temp 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage 100.0 milliamperes ac resistive load Main Contact Maximum Voltage Rating In Volts:	General
Winding Dc Resistance Rating: 765.0 ohms single winding Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Storage Type: General purpose warehouse Features Provided: Polarized Cubic Measure: 0.317 cubic inches Mounting Facility Pattern: In-line single mounting facility Operating Voltage Rating And Type At Specificationified Tem 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage 100.0 milliamperes ac resistive load Main Contact Maximum Voltage Rating In Volts:	Coil Quantity:
Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Storage Type: General purpose warehouse Features Provided: Polarized Cubic Measure: 0.317 cubic inches Mounting Facility Pattern: In-line single mounting facility Operating Voltage Rating And Type At Specificationified Tem 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage 100.0 milliamperes ac resistive load Main Contact Maximum Voltage Rating In Volts:	1
Duty Type: Continuous Arc Quenching Method: Air Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility Storage Type: General purpose warehouse Features Provided: Polarized Cubic Measure: 0.317 cubic inches Mounting Facility Pattern: In-line single mounting facility Operating Voltage Rating And Type At Specificationified Tem 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage 100.0 milliamperes ac resistive load Main Contact Maximum Voltage Rating In Volts:	Winding Dc Resistance Rating:
Continuous  Arc Quenching Method: Air  Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility  Storage Type: General purpose warehouse Features Provided: Polarized  Cubic Measure: 0.317 cubic inches  Mounting Facility Pattern: In-line single mounting facility  Operating Voltage Rating And Type At Specificationified Temp 26.5 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage 100.0 milliamperes ac resistive load  Main Contact Maximum Voltage Rating In Volts:	765.0 ohms single winding
Arc Quenching Method: Air  Mounting Facility Type And Quantity: 2 unthreaded hole single mounting facility  Storage Type: General purpose warehouse Features Provided: Polarized  Cubic Measure: 0.317 cubic inches  Mounting Facility Pattern: In-line single mounting facility  Operating Voltage Rating And Type At Specificationified Tem 26.5 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage 100.0 milliamperes ac resistive load  Main Contact Maximum Voltage Rating In Volts:	Duty Type:
Mounting Facility Type And Quantity:  2 unthreaded hole single mounting facility  Storage Type:  General purpose warehouse  Features Provided:  Polarized  Cubic Measure:  0.317 cubic inches  Mounting Facility Pattern:  In-line single mounting facility  Operating Voltage Rating And Type At Specificationified Temp  26.5 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage  100.0 milliamperes ac resistive load  Main Contact Maximum Voltage Rating In Volts:	Continuous
Mounting Facility Type And Quantity:  2 unthreaded hole single mounting facility  Storage Type:  General purpose warehouse  Features Provided:  Polarized  Cubic Measure:  0.317 cubic inches  Mounting Facility Pattern:  In-line single mounting facility  Operating Voltage Rating And Type At Specificationified Temp  26.5 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage  100.0 milliamperes ac resistive load  Main Contact Maximum Voltage Rating In Volts:	Arc Quenching Method:
2 unthreaded hole single mounting facility  Storage Type: General purpose warehouse  Features Provided: Polarized  Cubic Measure: 0.317 cubic inches  Mounting Facility Pattern: In-line single mounting facility  Operating Voltage Rating And Type At Specificationified Temple 26.5 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage 100.0 milliamperes ac resistive load  Main Contact Maximum Voltage Rating In Volts:	Air
Storage Type: General purpose warehouse Features Provided: Polarized Cubic Measure: 0.317 cubic inches Mounting Facility Pattern: In-line single mounting facility Operating Voltage Rating And Type At Specificationified Temp 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage 100.0 milliamperes ac resistive load Main Contact Maximum Voltage Rating In Volts:	Mounting Facility Type And Quantity:
General purpose warehouse  Features Provided:  Polarized  Cubic Measure:  0.317 cubic inches  Mounting Facility Pattern:  In-line single mounting facility  Operating Voltage Rating And Type At Specificationified Temp  26.5 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage  100.0 milliamperes ac resistive load  Main Contact Maximum Voltage Rating In Volts:	2 unthreaded hole single mounting facility
Features Provided: Polarized Cubic Measure: 0.317 cubic inches Mounting Facility Pattern: In-line single mounting facility Operating Voltage Rating And Type At Specificationified Temp 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage 100.0 milliamperes ac resistive load Main Contact Maximum Voltage Rating In Volts:	Storage Type:
Polarized  Cubic Measure:  0.317 cubic inches  Mounting Facility Pattern: In-line single mounting facility  Operating Voltage Rating And Type At Specificationified Tem  26.5 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage  100.0 milliamperes ac resistive load  Main Contact Maximum Voltage Rating In Volts:	General purpose warehouse
Cubic Measure:  0.317 cubic inches  Mounting Facility Pattern: In-line single mounting facility  Operating Voltage Rating And Type At Specificationified Temp  26.5 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage  100.0 milliamperes ac resistive load  Main Contact Maximum Voltage Rating In Volts:	Features Provided:
0.317 cubic inches  Mounting Facility Pattern: In-line single mounting facility  Operating Voltage Rating And Type At Specificationified Temp 26.5 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage 100.0 milliamperes ac resistive load  Main Contact Maximum Voltage Rating In Volts:	Polarized
Mounting Facility Pattern: In-line single mounting facility Operating Voltage Rating And Type At Specificationified Temp 26.5 volts dc 25 degrees celsius single winding Main Contact Load Current Rating At Maximum Rated Voltage 100.0 milliamperes ac resistive load Main Contact Maximum Voltage Rating In Volts:	Cubic Measure:
In-line single mounting facility  Operating Voltage Rating And Type At Specificationified Temp  26.5 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage  100.0 milliamperes ac resistive load  Main Contact Maximum Voltage Rating In Volts:	0.317 cubic inches
Operating Voltage Rating And Type At Specificationified Temperature 26.5 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage 100.0 milliamperes ac resistive load  Main Contact Maximum Voltage Rating In Volts:	Mounting Facility Pattern:
26.5 volts dc 25 degrees celsius single winding  Main Contact Load Current Rating At Maximum Rated Voltage  100.0 milliamperes ac resistive load  Main Contact Maximum Voltage Rating In Volts:	In-line single mounting facility
Main Contact Load Current Rating At Maximum Rated Voltage 100.0 milliamperes ac resistive load Main Contact Maximum Voltage Rating In Volts:	Operating Voltage Rating And Type At Specificationified Temp:
100.0 milliamperes ac resistive load  Main Contact Maximum Voltage Rating In Volts:	26.5 volts dc 25 degrees celsius single winding
Main Contact Maximum Voltage Rating In Volts:	Main Contact Load Current Rating At Maximum Rated Voltage:
	100.0 milliamperes ac resistive load
115.0 ac and 28.0 dc	Main Contact Maximum Voltage Rating In Volts:
	115.0 ac and 28.0 dc

## NSN 5945-00-060-2248

Electromagnetic Relay - Page 2 of 2



Terminal Type A	nd Quantity:
-----------------	--------------

8 pin all functions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03300