NSN 5945-00-064-7396

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-064-7396

| Thread Class: |
|--|
| 2a single mounting facility |
| Overall Length: |
| Between 1.880 inches and 1.920 inches |
| Overall Height: |
| 2.906 inches |
| Overall Width: |
| Between 1.460 inches and 1.500 inches |
| Environmental Protection: |
| Hermetic |
| Winding Quantity: |
| 1 |
| Coil Quantity: |
| 1 |
| Duty Type: |
| Continuous |
| Mounting Facility Type And Quantity: |
| 3 threaded stud single mounting facility |
| Thready Qty Per Inch (tpi): |
| 32 single mounting facility |
| Thread Size: |
| 0.138 inches single mounting facility |
| Mounting Facility Pattern: |
| Triangle single mounting facility |
| Nonpile-up Main Contact Arrangement: |
| 3 pole, double throw, one position momentary |
| Time Delay: |
| 1.50 seconds fixed operate time |
| Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle: |
| 1.870 inches single mounting facility |
| Operating Voltage Rating And Type At Specificationified Temp: |
| 48.0 volts dc 25 degrees celsius single winding |
| Main Contact Load Current Rating At Maximum Rated Voltage: |
| 5.0 amperes ac resistive load |
| Thread Series Designator: |
| Unc single mounting facility |
| Terminal Type And Quantity: |
| 10 wire hook all functions |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

--

NSN 5945-00-064-7396

Electromagnetic Relay - Page 2 of 2



Demilitarization:

No

Fiig:

A03300