NSN 5945-00-068-4219



Electromagnetic Relay - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5945-00-068-4219 **Thread Class:** 2b second mounting facility **Thread Direction:** Right-hand second mounting facility **Overall Length:** 3.250 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.750 inches second mounting facility **Overall Height:** 4.520 inches **Overall Width:** 3.090 inches **Case Material: Plastic Environmental Protection:** Dustproof **Unthreaded Mounting Hole Diameter:** 0.199 inches first mounting facility Center To Center Distance Between Mounting Facilities Parallel To Height: 0.500 inches second mounting facility **Fragility Factor:** Moderately rugged Frequency In Hertz: 60.0 Winding Quantity: **Purpose For Which Designed:** General **Coil Quantity:**

Duty Type:

Continuous

Arc Quenching Method:

Air

Mounting Facility Type And Quantity:

6 unthreaded hole first mounting facility

Storage Type:

General purpose warehouse

Cubic Measure:

45.392 cubic inches

Thready Qty Per Inch (tpi):

32 second mounting facility

NSN 5945-00-068-4219

Electromagnetic Relay - Page 2 of 2

Fiig: A03300



Thread Size:
0.164 inches second mounting facility
Mounting Facility Pattern:
Rectangular second mounting facility
Nonpile-up Main Contact Arrangement:
2 pole, double throw, one position momentary
Time Delay:
1.50 seconds fixed operate and release time and 15.00 seconds fixed operate and release time
Operating Voltage Rating And Type At Specificationified Temp:
120.0 volts ac 25 degrees celsius single winding
Main Contact Load Current Rating At Maximum Rated Voltage:
10.0 amperes ac resistive load and 15.0 amperes dc resistive load
Main Contact Maximum Voltage Rating In Volts:
240.0 ac and 30.0 dc
Energizing Element Power Rating:
8.0 watts
Thread Series Designator:
Unc second mounting facility
Terminal Type And Quantity:
8 screw all functions
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No