## NSN 5945-00-069-1275

Electromagnetic Relay - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5945-00-069-1275

1.160 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches single mounting facility

**Center To Center Distance Between Mounting Facilities Parallel To Width:** 

0.125 inches single mounting facility

**Overall Height:** 

0.400 inches

**Overall Width:** 

0.875 inches

**Environmental Protection:** 

Hermetic

**Unthreaded Mounting Hole Diameter:** 

0.096 inches single mounting facility

Winding Quantity:

2

**Coil Quantity:** 

2

Winding Dc Resistance Rating:

700.0 ohms second winding

**Duty Type:** 

Continuous

**Mounting Facility Type And Quantity:** 

4 unthreaded hole single mounting facility

**Features Provided:** 

Polarized

**Mounting Facility Pattern:** 

Rectangular single mounting facility

Nonpile-up Main Contact Arrangement:

2 pole, double throw, one position momentary

**Operating Current Rating And Type:** 

39.0 milliamperes dc all windings

Time Delay:

0.0050 seconds fixed operate time

**Operating Voltage Rating And Type At Specificationified Temp:** 

26.5 volts dc 25 degrees celsius all windings

Main Contact Load Current Rating At Maximum Rated Voltage:

1.0 amperes ac resistive load and 2.0 amperes dc resistive load

Main Contact Maximum Voltage Rating In Volts:

115.0 ac and 29.0 dc

**Terminal Type And Quantity:** 

10 pin all functions

## NSN 5945-00-069-1275

Electromagnetic Relay - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03300